

BHARATBENZ



WITH THE POWER OF OUR **BSVI** RANGE LEAD THE CHANGE **SO28TT (4×2)**

BHARATBENZ

0

5028









Your BharatBenz comes with a pool of best in class features

Safety

- Driver State Monitoring System (Optional): Identifies and alerts drivers from falling asleep or being distracted at the wheel.
- Seatbelt Reminder: Ensures superior safety to the occupants.
- **Diffuser Tailpipe:** Helps in exhaust temperature management and reduction of dust throw.
- Daytime Running Lamp: Ensures vehicle visibility during daytime as well.

Comfort

- Heating, Ventilation & AC (HVAC): High throw air conditioning and climate control for all extreme weathers.
- Air Suspended Seat (Optional): Ensures maximum driving comfort even in rugged terrains.
- Music System: For entertainment and information on the go.
- **Power Windows:** Windows that can be raised or lowered just with the press of a button.
- Central Locking: Locks the whole cabin with just a flick of the driver-side lock handle.
- Static Steering: Enables easier maneuverability during tight turns.



ENGINE

Designed for higher efficiency, longer life and maximum power with optimal fuel consumption to enable you to maximize your revenues.



3 PIECE BUMPER

In the event of collision, only the damaged part has to be replaced. Thus reducing the maintenance cost.



GEAR SHIFT ADVISOR

Provides up/down indication of the gear shift to ensure optimal operation of the vehicle.



SOFT CRUISE

Improved cruise control that not only ensures better driver comfort but also provides improved fuel efficiency through intelligent gradient monitoring.



ENGINE BRAKE

When the engine brake is on, the constant throttle valve and the butterfly valve work in tandem to save fuel, reduce brake wear and make driving in downhill operations safer.



TILT AND TELESCOPIC STEERING

The tilt/telescopic feature allows the drive to adjust the steering wheel to suit their driving posture.



TURBOCHARGER

High boost turbocharger ensures the perfect blend of air and fuel mixture, thus reducing fuel consumption.



DIFFERENTIAL LOCK

Avoids the wheel spinning on slushy roads, enabling faster trip turnaround time.



FUEL THEFT PROTECTION MESH

A meshed grill is placed at the mouth of the fuel tank to prevent any fuel theft between trips.





ELECTRONIC BRAKE FLAP

Electronically controlled system that accurately controls the exhaust brake flap to ensure efficient thermal management within the engine thereby improving fuel efficiency



G131 WITH OPTIMAL GEAR RATIOS

Optimal gear ratios to improve gradeability and also fuel efficiency by ensuring higher operating time in top gears.



THICKER AND DURABLE FRAME

In frame, 9mm thick frame and high strength BSK46 steel ensures higher durability and reliability.



POWER REDUCTION (PR) COMPRESSOR

The new optimized compressor operates based on the engine duty cycle to ensure better fuel efficiency.



LONG LASTING CABIN PAINT

With 800 hours of UV testing done for better cabin paint reliability.



ADVANCED AERODYNAMIC CABIN

Offers the lowest drag and add-on bumper spoiler with splitter for improved aerodynamics.



Ensures fewer number of visits to the dealership thus reducing cost of maintenance.



HUB REDUCTION AXLE

Intelligently designed axle offering lower weight but high durability and reliability for greater up time.



ANTI-ROLL BAR (Std - on both Axles)

The anti-roll bar increases vehicle stability on application with high centre of gravity. This improves driving confidence and safety especially during cornering at high speeds.



ENGINE OVERRUN BUZZER

The inbuilt buzzer system detects engine overspeeding resulting from sudden downshifting of gears (lower than the recommended shift) and provides an acoustic alarm to alert the driver. This helps prevent engine damage.

Designed to Deliver.

The major applications suitable for BharatBenz 5028TT include the below mentioned:






BULKER

Technical Specifications

Vehicle Dimensions	
Wheel Base (mm)	3600
Cabin	Sleeper
Overall Length (mm)	6063m
Overall Width (mm)	2490
Overall Height (mm) (CBC)	2975
Front Overhang (mm)	1485
Rear Overhang (mm)	978
Ground Clearance (mm)	304
Engine	
Engine Model	OM 926
Maximum Power, KW	210Kw @2200 rpm
Maximum Torque, Nm	1100Nm @ 1200 - 1600 rpm
No. of Cylinders, CC	6, 7200
Emission Std	Bharat Stage VI
Transmission	
Gear Box Model & Type	G 131, 9F+1R, Mechanical, Synchromesh Gears
Clutch Type	Single Dry Plate, Hydraulic Control
Clutch Dia, (mm)	430, 4.5 mm High Wear
Power Take-off	Gearbox PTO Spline (Standard fitment)
Axle	
Front Axle	IF 7.0
Rear Axle	MT36 610 (Hub Reduction)
RAR*	4.55
Chassis Frame & Suspension	T.00
Frame Section	
(D X W X T) (mm)	288 x 70 x 9
Front Suspension	Parabolic Type Leaf Spring with 2 Hydraulic Shock Absorbers
Rear Suspension	Semi-Elliptical Leaf Spring
Anti-Roll Bar	Standard on on both Axles (PTO Variants)
Brakes	
Service Brake	Pneumatic, Foot Operated, Dual Line with ABS
Parking Brake	Pneumatically Operated Hand Control Valve
Front Axle Brake	Ø 410 drum
Rear Axle Brake	Ø 410 drum
Steering	
Steering Type	Hydraulic Power Assisted
Fuel Tank & Electricals	<u>,</u>
Fuel Tank / Filling Capacity*	455L/430L
Adblue Tank	60L/ 51L
Battery Capacity	120Ah
Voltage	24V
Performance	211
Maximum Gradeability %	24.3
Maximum Gradeability 70 Maximum Geared Speed kmph	80kmph
TCD*	13.1 m
Tyres (Size, Pattern)	
Pattern and Size	Padial Turas (11P20 & 205/00P20) Tubalasa Turas (205/20P22 5)
	Radial Tyres (11R20 & 295/90R20) Tubeless Tyres (295/80R22.5)
Weight	(with Suitable Three Ayle Trailer, greater than 2m pan tridem apacing P
Gross Combination	(with Suitable Three Axle Trailer - greater than 3m non-tridem spacing & mechanical suspension on all trailer axles) Radial (11R20) & Tubeless,
Weight - GCW	295/90R20 Tyres - 49,960Kgs & 50,000Kgs
	200,000 20 19100 - 10,0001 (go (c 00,0001 (go

Note: Unique trailer to the built as per recommended bodybuilding guidelines for 5028T models (refer Oprators Service Book)

Globally Proven SCR Technology




Your truck at your fingertips

TRUCK ONNECT

With Truckonnect, an interactive portal that uses real-time vehicle data, you can monitor and analyse your fleet and processes. The core objective of Truckonnect is to increase uptime, provide 24/7 support service, monitor real-time fleet performance and ensure the drivers' safety.



The All-round Services Package for your Truck



Ensuring Safe Journeys



Ensuring Safe Journeys

As a promise to offer a safe and hygienic cabin on our MDT and HDT trucks, we have introduced 3 safety features as part of the standard offering (Curtains in HDT Sleeper Cabin, Infection Resistant Fabric on Seat and Healthcare Kit for Drivers) and 2 additional features as accessories for sale at the dealer's end (Disinfectant Fogging Machine and UV Sterilizer Box).








Note: * Accessories only and not part of Standard fitment.

Within Reach. No Matter Where You Are.

We believe that the customer's convenience is paramount. Area sales offices in 14 leading cities and a network covering 236 locations mean that you can quickly purchase a BharatBenz truck, whenever and wherever the need arises. We are already setting benchmarks in the Indian trucking industry with well-trained sales staff, highly qualified service personnel, customized services and products and state-of-the-art infrastructure.

We are committed to delivering a superlative experience across the length and breadth of India.



Daimler India Commercial Vehicles Pvt. Ltd.

SIPCOT Industrial Growth Centre, Oragadam, Mathur Post, Sriperumbudur Taluk, Kancheepuram District - 602105, Tamil Nadu, India. Toll Free No. : 1800-120-380380 (Service), 1800-121-380380 (Sales), 1800-120-381381 (Parts) Website: www.bharatbenz.com



All specifications and technical data present are only indicative in nature and can be changes or revised by OEM at any given point of time.