

## PROFIT

WITH THE POWER OF OUR **BSVI** RANGE

LEAD THE CHANGE **45T** (**4**×**2**) TRACTOR







## **Technical Specifications** 4628T 4x2 Vehicle Dimensions Wheel Base (mm) 3600 Cabin Sleeper Cabin Overall Length (mm) 6063 Overall Width (mm) 2490 Overall Height (mm) (CBC) 2920 Front Overhang (mm) 1485 Rear Overhang (mm) 978 304 Ground Clearance (mm) **E**ngine OM 926 **Engine Model** Maximum Power, kW 210 kW @ 2200 rpm Maximum Torque, Nm 1100 Nm @ 1200 - 1600 rpm No. of Cylinders, cc 6,7200 **Emission Standard** Bharat Stage VI - OBD-2 **Transmission** Gear Box Model & Type G 131, 9F+1R, Mechanical, Synchromesh Gears Clutch Type Single Dry Plate, Hydraulic Control Clutch Dia, Wear (mm) 430, 4.5 mm Power Take Off **Auxiliary Fitment** Axle Front Axle IF 7.0 Rear Axle IR440 (Single Reduction Axle) Rear Axle Ratio 4.3 **Chassis Frame & Suspension** Frame Section (D X W X T) mm 288 x 70 x 9 Front Suspension Parabolic Type Leaf Spring with 2 Hydraulic Shock Absorbers Rear Suspension Semi-Elliptical With Auxiliary Springs Anti-roll Bar Front: Standard **Brakes** Service Brake Pneumatic, Foot Operated, Dual Line with ABS Parking Brake Pneumatically Operated Hand Control Valve Front Brake Size (mm) & Type Ø 410 drum Rear Brake Size (mm) & Type Ø 410 drum Steering Steering Type Hydraulic Power Assisted Fuel & Electrical System 455L/430L Fuel Tank / Filling Capacity 60L/51L Adblue Tank / Filling Capacity **Battery Capacity** 120Ah 24V Voltage

PerformanceMaximum Gradeability %27.60%Maximum Geared Speed kmph80 kmp

Weight

Maximum Geared Speed kmph
TCD 80 kmph
Tyres

Pattern & Size Radial Tyres - 295/90R20

Gross Vehicle Weight - GVW

43500 kgs - with suitable 2 axle trailer;
45500 kgs - with suitable 3 axle trailer